

FOXTAM Range of Current Transformers

FEATURES

- MOULDED CASE
- PRIMARY WOUND VERSIONS
- BUS-BAR VERSIONS
- DIN RAIL MOUNTED VERSIONS
- SUMMATION CT's
- SPLIT CORE CT's
- TRIPLE THREE PHASE CT's
- SLIDING SEALABLE TERMINAL COVERS
- P1 & P2 PRIMARY DESIGNATION WITHIN MOULDING
- S1 & S2 SECONDARY DESIGNATION WITHIN MOULDING
- 1 AMP & 5 AMP SECONDARIES
- CLASS 1 AS STANDARD (CLASS 0.5 & 0.2 ON REQUEST)

SPECIFICATIONS

Compliance:	IEC185, BS7626, BSED 60044-1, IEC 60044-1
CEmarked:	Yes
Rated system voltage:	Max 720V continuous
Insulation:	Max 3KV for 1 min
Frequency range:	50-60Hz (400Hz on requested)
Ambient temperature range:	-30°C to 85°C (Triple Three Phase & Split Core CT's max 80°C)
Continuous current:	1.2 x rated current

FOX.WP

Moulded case Primary Wound current transformers for primary currents from 1 Amp to 40 Amps. With built in terminal covers and M6 terminals for the primary current connection.

FEATURES

- DIN RAIL OR FOOT MOUNTED
- BUILT IN HINGED SEALABLE TERMINAL COVERS
- TRANSFORMER WIDTH 60mm
- PRIMARY RANGES FROM 1 AMP TO 40 AMPS
- 1 AMP OR 5 AMP SECONDARIES



P/No.	CLASS	VA
FOX.WP 1/1	1	5
FOX.WP 1/5	1	5
FOX.WP 5/5	1	5
FOX.WP 10/5	1	5
FOX.WP 15/5	1	5
FOX.WP 20/5	1	5
FOX.WP 25/5	1	5
FOX.WP 30/5	1	5
FOX.WP 40/5	1	5

