

FOXTAM Range of Current Transformers

FEATURES

- MOULDED CASE
- PRIMARY WOUND VERSIONS
- BUS-BAR VERSIONS
- DIN RAIL MOUNTED VERSIONS
- SUMMATION CT's
- SPLIT CORE CT's
- TRIPLE THREE PHASE CT's
- SLIDING SEALABLE TERMINAL COVERS
- P1 & P2 PRIMARY DESIGNATION WITHIN MOULDING
- S1 & S2 SECONDARY DESIGNATION WITHIN MOULDING
- 1 AMP & 5 AMP SECONDARIES
- CLASS 1 AS STANDARD (CLASS 0.5 & 0.2 ON REQUEST)

SPECIFICATIONS

| | |
|----------------------------|---|
| Compliance: | IEC185, BS7626, BSED 60044-1, IEC 60044-1 |
| CEmarked: | Yes |
| Rated system voltage: | Max 720V continuous |
| Insulation: | Max 3KV for 1 min |
| Frequency range: | 50-60Hz (400Hz on requested) |
| Ambient temperature range: | -30°C to 85°C (Triple Three Phase & Split Core CT's max 80°C) |
| Continuous current: | 1.2 x rated current |



FOX100.55

Moulded case current transformers, for primary currents from 600 Amps to 4000 Amps. With built in sliding sealable terminal covers.

FEATURES

- BUS-BAR OR FOOT MOUNTED
- BUILT IN SLIDING SEALABLE TERMINAL COVERS
- TRANSFORMER WIDTH 129mm
- MAX BUS-BAR SIZE 100x55mm
- 1 AMP OR 5 AMP SECONDARIES



| P/No. | CLASS | VA |
|------------------|-------|----|
| FOX100.55 600/5 | 1 | 10 |
| FOX100.55 800/5 | 1 | 15 |
| FOX100.55 1000/5 | 1 | 15 |
| FOX100.55 1200/5 | 1 | 15 |
| FOX100.55 1500/5 | 1 | 15 |
| FOX100.55 1600/5 | 1 | 15 |
| FOX100.55 2000/5 | 1 | 15 |
| FOX100.55 2500/5 | 1 | 15 |
| FOX100.55 3000/5 | 1 | 15 |
| FOX100.55 4000/5 | 1 | 15 |

All of the above ratios are available as Class 0.5 and Class 0.2 to special order; please consult our sales office.

FOX100.55 DIMENSIONS

