

FOXTAM Range of Current Transformers

FEATURES

- MOULDED CASE
- PRIMARY WOUND VERSIONS
- BUS-BAR VERSIONS
- DIN RAIL MOUNTED VERSIONS
- SUMMATION CT's
- SPLIT CORE CT's
- TRIPLE THREE PHASE CT's
- SLIDING SEALABLE TERMINAL COVERS
- P1 & P2 PRIMARY DESIGNATION WITHIN MOULDING
- S1 & S2 SECONDARY DESIGNATION WITHIN MOULDING
- 1 AMP & 5 AMP SECONDARIES
- CLASS 1 AS STANDARD (CLASS 0.5 & 0.2 ON REQUEST)

SPECIFICATIONS

| | |
|----------------------------|---|
| Compliance: | IEC185, BS7626, BSED 60044-1, IEC 60044-1 |
| CEmarked: | Yes |
| Rated system voltage: | Max 720V continuous |
| Insulation: | Max 3KV for 1 min |
| Frequency range: | 50-60Hz (400Hz on requested) |
| Ambient temperature range: | -30°C to 85°C (Triple Three Phase & Split Core CT's max 80°C) |
| Continuous current: | 1.2 x rated current |



FOX75

Moulded case "triple" current transformer with apertures on 25mm centres, giving an overall width of 75mm allowing installation directly on top of moulded case circuit breakers.

FEATURES

- FOOT MOUNTED
- WITH TERMINAL COVER
- TRANSFORMER WIDTH 75mm
- MAX CABLE SIZE 15mm DIA
- MAX BUS-BAR SIZE 15mm WIDTH
- 1 AMP OR 5 AMP SECONDARIES



| P/No. | CLASS | VA |
|-------------|-------|-----|
| FOX75 60/5 | 1 | 1 |
| FOX75 100/5 | 1 | 1.5 |
| FOX75 150/5 | 1 | 2.5 |

FOX75 DIMENSIONS

