

FOX.SC23


- FEATURES
- PROTECTED TERMINALS
- INTEGRAL CABLE / BUS-BAR PINCH SCREWS
- PRIMARIES FROM 100 AMPS TO 400 AMPS
- MAX APERTURE SIZE 23x33mm
- MAX OVERALL DIMENSIONS 93x106mm
- CLASS 1 (class 0.5 on request, some ratios)
- 1 AMP OR 5 AMP SECONDARIES



P/No.	CLASS	VA
FOX.SC23 100/5	1	1.5
FOX.SC23 150/5	1	1.75
FOX.SC23 200/5	1	2.5
FOX.SC23 250/5	1	3.75
FOX.SC23 300/5	1	5
FOX.SC23 400/5	1	6.25

1 Amp secondaries available to special order, along with Class 0.5 on some ratios, please consult our sales office.

DIMENSIONS



FOX.SC58

- FEATURES
- PROTECTED TERMINALS
- INTEGRAL CABLE / BUS-BAR PINCH SCREWS
- PRIMARIES FROM 250 AMPS TO 1000 AMPS
- MAX APERTURE SIZE 82x52mm
- MAX OVERALL DIMENSIONS 125x158mm
- CLASS 1 (class 0.5 on request)
- 1 AMP OR 5 AMP SECONDARIES



P/No.	CLASS	VA
FOX.SC58 250/5	1	2.5
FOX.SC58 300/5	1	3.75
FOX.SC58 400/5	1	3.75
FOX.SC58 500/5	1	5
FOX.SC58 600/5	1	7.5
FOX.SC58 800/5	1	10
FOX.SC58 1000/5	1	15

1 Amp secondaries available to special order, along with Class 0.5 on some ratios, please consult our sales office.

DIMENSIONS

